



ANTI GRAFFITI COATING Graffiti Remover

Anti Graffiti Coating graffiti remover can be used to remove graffiti that has been placed on surfaces protected with our Smart Epoxy Coating product.



Note: DO NOT USE a power washer on any surface that has been protected with Smart Epoxy Coating. Please only use a bucket of water and a white towel rag and AGC graffiti remover to remove graffiti.

SAFETY INSTRUCTIONS

When starting a graffiti removal job always wear safety protection before handling any of the graffiti removing products. Safety goggles and chemical resistant gloves are required before using Anti Graffiti Coating Graffiti Remover. Wearing long sleeves and long pants are recommended to protect the skin. Always have access to water when working with Anti Graffiti Coating Graffiti Remover. If Anti Graffiti Coating Graffiti Remover does get on your skin, wash the skin with water to remove the product.

Before using Anti Graffiti Coating Graffiti Remover check the surface to see how clean it is. The surface does not have to be perfectly clean to start, but if the surface has substantial dirt on it, the dirt may impede the penetration process and should be washed off before removing the graffiti.

(Note: Always test product on a small hidden area prior to full application.)

Smart Graffiti Ireland. Apple View, Trim Road, Kildalkey, Co. Meath, C15 W702, Ireland
Tel: Ireland +353 (0)86 8111187
Email: sales@smartgraffiti.eu
www.smartgraffiti.eu

Exterior and Interior Graffiti Removal Process: Equipment

Needed for Removal of Graffiti:

1. Anti Graffiti Coating Graffiti Remover
2. Safety equipment (goggles, chemical resistant gloves, etc.)
3. Bucket of water
4. Rags

Application Method:

1. Put your chemical resistant gloves and goggles on
2. Wash down the surface with water using a rag
3. Dab the product liberally on the graffiti
4. Let the product activate on the surface for 60 seconds
5. Agitate surface with wipe
6. Wash off with water using a new rag
7. Repeat steps if graffiti is still showing

At the end of the job, wash down all safety equipment and tools used in the removal process to get all of the Anti Graffiti Coating Graffiti Remover off for reuse on the next job.

Results and Benefits:

The main differences between Anti Graffiti Coating Graffiti Remover and other graffiti removal methods include: dramatically reducing the time it takes to remove the graffiti, one application's effectiveness in removing 99% of the typical graffiti and no damage to the original underlying surface! Anti Graffiti Coating Graffiti Remover gets all of the graffiti off the surface within minutes while other products can take multiple applications and hours of time. Anti Graffiti Coating Graffiti Remover enables removal in minutes on all the typical surfaces which have protection with our Smart Epoxy Coating which saves our customers significant time and labour. With less time and labour spent on each individual graffiti removal job, our customers can get 2, 3 even 4 times as many graffiti removal jobs accomplished per shift.

Anti Graffiti Coating Graffiti Remover is most effective when used in a "wet surface" removal process. By "wet surface process" we are referring to the practice of starting with a water wetted surface and keeping the work surface wet at all times as Anti Graffiti Coating Graffiti Remover is applied, loosens the graffiti and then power washed off with the graffiti.

Coverage:

Varies dependent upon type of surface material 0.2 -0.5 litre/m²

With Wipes the coverage can be 0.1 -0.3 litre/m²